METALWORKING FLUIDS

EXTREMECUT.

A hand applied reaming, tapping, and drilling lubricant based on highly effective extreme pressure and lubricity additives to promote ease of cutting and prolong tool life.

PRODUCT RANGE
Tapping & Reaming Oils

APPLICATION

- Reaming
- Tapping
- Drilling
- Hand-applied via squeeze or dripping bottle
- High alloy steels
- Non-ferrous metals

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Brown viscous fluid**
Specific Gravity @ 15°C		**1.14 – 1.18**
Viscosity @ 40°C, cSt		**170 – 200**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0418

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063