COMMERCIAL VEHICLES

FLEETLUBE 15W-40.

Engine oil designed to meet the requirements of both turbocharged and naturally aspirated diesel and petrol engines.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

108.9 cSt	14.2 cSt	0.881	220 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Mixed older commercial fleets
- Turbocharged and naturally aspirated engines
- Plant, generators and agricultural machinery

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 7 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 15W-40**
Base Oil		**Mineral**
Specific Gravity @ 15.6°C		**0.881**
Kinematic Viscosity @ 40°C, cSt		**108.9**
Kinematic Viscosity @ 100°C, cSt		**14.2**
Viscosity Index	ASTM D2270	**141**
Flash Point (COC), °C		**220**
Pour Point, °C	ASTM D97	**-32**
TBN, mg KOH/g	ASTM D2896	**9.18**

Typical values. They do not form a specification.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CG-4/SJ
ACEA	E3
MB	228.3
Volvo	VDS
Mack	EO-M
MAN	271
Daimler Truck	DTFR 15B110

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0008M

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063