COMMERCIAL VEHICLES

FLEETLUBE HD 15W-40.

Engine oil designed to meet the requirements of turbocharged and naturally aspirated diesel and petrol engines.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

108.0 cSt	15.5 cSt	0.882	217 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Older mixed fleets
- General plant and agricultural use
- Naturally aspirated diesel engines

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CF-4/SG

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 15W-40**
Base Oil		**Mineral**
Specific Gravity @ 15.6°C		**0.882**
Kinematic Viscosity @ 40°C, cSt		**108.0**
Kinematic Viscosity @ 100°C, cSt		**15.5**
Viscosity Index	ASTM D2270	**152**
Flash Point, °C	ASTM D92	**217**
Pour Point, °C	ASTM D97	**-30**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0012

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063