COMMERCIAL VEHICLES

FLEETSTAR 15W-40.

Heavy duty diesel engine oil for long haul and mixed fleet operators requiring maximum protection under demanding conditions.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

105.0 cSt	13.9 cSt	0.900	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.5	Flash point

APPLICATION

- Long haul and mixed fleet operation
- Older commercial vehicles
- Plant and generating sets

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 13 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CH-4/SL
ACEA	E7/E5/E3/A3/B4
MB	228.3
Volvo	VDS-2
Cummins	20071/72/76/77/78
MAN	3275
MTU	Type 2
Renault	RLD-2
Mack	E-OM+
Caterpillar	ECF-1
ZF	TE-ML 07C/04C
Global	DHD-1
Daimler Truck	DTFR 15C100

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 15W-40**
Base Oil		**Mineral**
Kinematic Viscosity @ 40°C, cSt		**105.0**
Kinematic Viscosity @ 100°C, cSt		**13.9**
Viscosity Index	ASTM D2270	**133**
Pour Point, °C	ASTM D97	**-31**
Flash Point, °C	ASTM D92	**210**
Specific Gravity @ 15.5°C		**0.900**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0700

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

British expertise engineered into every drop.