COMMERCIAL VEHICLES

FLEETSTAR PERFORMANCE PLUS 10W-30.

Semi-synthetic heavy duty diesel engine oil, especially suitable for vehicles equipped with after-treatment systems.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

12.1 cSt	0.867	223 °C	-36 °C
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Pour point

APPLICATION

- After-treatment equipped vehicles
- Fuel-economy sensitive fleet operation
- Mixed on/off-highway duty

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

COMMERCIAL VEHICLES · CONTINUED

FLEETSTAR PERFORMANCE PLUS 10W-30.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CK-4/CJ-4/SN
ACEA	E11/E7/E9
Volvo	VDS-4.5
Renault	RLD-3
Mack	EOS-4.5
MB	228.31
Cummins	CES 20086/20081
MAN	M3775/M3575
Caterpillar	ECF-3
JASO	DH-2
Allison	TES 439
Ford	M2C171-F/M2C171-E
Deutz	DQC-III-10 LA
Detroit Diesel	DDC93K222/DDC93K218
Daimler Truck	DTFR 15C100

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-30**
Base Oil		**Semi-synthetic**
Kinematic Viscosity @ 100°C, cSt		**12.1**
Flash Point, °C	ASTM D92	**223**
Pour Point, °C	ASTM D97	**-36**
Specific Gravity @ 15.6°C		**0.867**
Sulphated Ash, % wt	ASTM D874	**< 1.0**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0441

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063