COMMERCIAL VEHICLES

FLEETSTAR PLUS LD 10W-40.

Fully synthetic low-SAPS heavy-duty diesel engine oil built for the longest drain intervals modern fleets run.

PRODUCT RANGE
Heavy Duty Diesel Engine Oils

APPLICATION

- Extended drain long-haul fleets
- Marine auxiliary engines
- Stationary and standby generating sets

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 5 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

MAN	M3277
ACEA	E4/E7
MB-Approval	228.5
Volvo	VDS-3
Scania	LDF-2

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Fully synthetic**
Density @ 15°C	ASTM D4052	**0.861 kg/l**
Flash Point, °C	ASTM D92	**228**
Pour Point, °C	ASTM D97	**-42**
TBN, mg KOH/g	ASTM D2896	**13.5**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0551

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063