COMMERCIAL VEHICLES

FLEETSTAR PREMIUM 15W-40.

One of the latest generation of heavy duty diesel engine oils, offering maximum protection under the most demanding conditions for engines that do not require a low SAPS formulation.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

106.0 cSt	14.2 cSt	0.887	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Mixed fleets, long-distance trunking and stop/start delivery
- Euro 3 and Euro 4 engines without after-treatment
- Certain Euro 5 engines without particulate filters

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CI-4/CH-4/SL
ACEA	E7/E5/A3/B4
MB	228.3
MAN	3275
Volvo	VDS-3
Renault	RLD-2
Mack	E-OM Plus
Cummins	20071/72/76/77/78
MTU	Type 2
Caterpillar	ECF-1a
Deutz	DQC III/II
Daimler Truck	DTFR 15B110

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 15W-40**
Base Oil		**Mineral**
Kinematic Viscosity @ 40°C, cSt		**106.0**
Kinematic Viscosity @ 100°C, cSt		**14.2**
Viscosity Index	ASTM D2270	**136**
Pour Point, °C	ASTM D97	**-31**
Flash Point, °C	ASTM D92	**210**
Specific Gravity @ 15.6°C		**0.887**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0010

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063