SPECIALITIES

Flexy Shield Open Gear Lube Aerosol.

Flexy Shield is formulated to be suitable for use on all exposed gears, wire ropes and moving parts and the anti-fling additives ensure it will not be thrown off during use.

PRODUCT RANGE
Aerosols & Sprays

APPLICATION

- exposed gears
- wire ropes and moving parts
- exposed heavy duty chains
- fifth wheels on trucks
- steel cables on overhead cranes
- situations with constant weather exposure

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PACK SIZES

500ml aerosol in box of 12

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS ARFLS500

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063