SPECIALITIES

FLUSHING OIL - AUTOMOTIVE.

Low-viscosity flushing fluid used to remove sludge and deposits from engines and gearboxes prior to an oil change.

PRODUCT RANGE
Flushing Oils

APPLICATION

- Pre-service engine flushing
- Gearbox and hydraulic flushing

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Workshop	grade

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity Grade	ISO 3448	**ISO VG 22**
Flash Point, °C	ASTM D92	**170**
Detergency		**High**
Use		**Pre-drain flush**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0009F

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063