COMMERCIAL VEHICLES

GEAR-PRO S 75W-85.

A low-viscosity, fully synthetic gear oil for modern driveline components, giving the fuel-economy benefit of a 75W-85 grade over conventional 80W/90W gear oils without giving up load-carrying performance.

PRODUCT RANGE

Transmission & Axle Oils

64.4 cSt	11.7 cSt	0.862	215 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Driveline components: transmissions, axles, transfer cases and final drives
- Limited-slip differentials
- Late-model passenger cars, vans, trucks and buses

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 17 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

COMMERCIAL VEHICLES · CONTINUED

GEAR-PRO S 75W-85.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-5 and GL-5 LS
SAE	J-2360
BMW	Hypoid Axle Oil G1/8222295532, Hypoid Axle Oil G2/8222413511, Hypoid Axle Oil G5/8222471487
BOT	448, BOT 799
DAIMLER	TRUCK DTFR 12B120 (previously MB 235.31)
FCA/FIAT	9.55550-DA8, 9.55550-DA9
FORD	M2C 942-A
HONDA	Hypoid Gear Oil HGO-1
LAND	ROVER LR052059, LR129319
LEXUS/TOYOTA	LSD Differential Oil LX
MOPAR	68083381AA
MERCEDES-BENZ	MB 235.15, MB 235.33, MB 235.62, MB 235.74
VW	G 052 190, G 052 518, G 055 190, G 060 190

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.862**
Viscosity @ 40°C, cSt		**64.4**
Viscosity @ 100°C, cSt	ASTM D445	**11.7**
Flash Point (COC), °C		**215**
Pour Point, °C	ASTM D97	**-51**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0661

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063