SPECIALITIES

H/OAT LONG LIFE ANTIFREEZE.

A hybrid OAT concentrate formulated for heavy duty diesel service.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Heavy duty diesel engines specified for hybrid coolant
- VAG G11 / G48 systems
- Aluminium-intensive engines needing fast surface protection
- Scania LLC TB1451 applications

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306, D6210
AFNOR	NF R15-601
SAE	J 1034
SCANIA	LLC TB1451
VAG	G11, TL 774-C
G48 specification fluid	

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Blue/Green Colour**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF00400

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063