GREASES

HAMMER GREASE.

A bentone-thickened, semi-synthetic, graphited grease developed specifically for hydraulic breakers.

PRODUCT RANGE
Heavy Plant Greases

1000 cSt	> 260 °C	2 / 3	Black
Viscosity @ 40°C	Dropping point	NLGI grade	Colour

APPLICATION

- Hydraulic breakers and hammers
- Pin and bush points on large earthmoving plant
- Demolition and quarrying equipment
- Impact-loaded joints running hot

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth Adhesive Grease**
Colour	ASTM D1500	**Black**
NLGI Classification		**2 / 3**
Thickener		**Bentone**
Base Oil		**Semi Synthetic**
Base Oil Viscosity @ 40°C (IP71), cSt		**1000**
Oil Separation (IP121), %		**2**
Worked Penetration (IP50)		**230 to 260**
Dropping Point (IP132), °C		**> 260**
Water Washout (ASTM D1264) @ 38°C, %		**2**
Water Washout (ASTM D1264) @ 79°C, %		**5**
Four Ball Weld Load (IP239)		**500 kgs**
Graphite Content, %		**10**
Operating Temperature Range, °C		**-5°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0500

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063