AUTOMOTIVE

HYPOID GEAR OILS 80W-90 GL-5.

A heavy duty hypoid axle lubricant formulated for a wide variety of gearboxes and axles requiring high levels of extreme pressure (EP) performance to API GL-5 specification.

PRODUCT RANGE
Gear & Axle Oils

155.0 cSt	17.0 cSt	0.894	200 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Wide variety of gearboxes and axles requiring high levels of extreme pressure (EP) performance

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.894**
Viscosity @ 40°C, cSt		**155.0**
Viscosity @ 100°C, cSt	ASTM D445	**17.0**
Viscosity Index	ASTM D2270	**118**
Flash Point (PMCC), °C		**200**
Pour Point, °C	ASTM D97	**–25**

Typical values. They do not form a specification.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-5
MIL-L-2105D	

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0021

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063