AUTOMOTIVE

HYPOID GEAR OILS SAE 90.

A conventional API GL-5 hypoid gear oil for axles and gearboxes needing extreme pressure performance.

PRODUCT RANGE
Gear & Axle Oils

156.0 cSt	17.1 cSt	0.898	200 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Monograde axle applications
- Classic and older vehicles
- Agricultural and plant axles

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Meets	or exceeds API GL-5 / MIL-L-2105D

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.898**
Viscosity @ 40°C, cSt		**156.0**
Viscosity @ 100°C, cSt	ASTM D445	**17.1**
Viscosity Index	ASTM D2270	**119**
Flash Point (PMCC), °C		**200**
Pour Point, °C	ASTM D97	**25**

Typical values. They do not form a specification.

PACK SIZES

20 L | 205 L | 1000 L IBC | Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0022

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063