SPECIALITIES

INSTANT DEGREASER.

A low viscosity solvent degreaser built on non-ionic and anionic surfactants with a coalescent additive.

PRODUCT RANGE
Cleaners & Degreasers

APPLICATION

- Degreasing components before repair or inspection
- Engine bays and chassis cleaning
- Workshop parts washing
- Removing aged grease films from machinery

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Clear Blue Liquid**
pH of Aqueous Solution	10% aqueous emulsion	**7**
Density @ 15.6°C		**0.810**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS ID0026

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063