GREASES

LITHIUM 0 EP.

A semi-fluid grease for centralised lubrication.

PRODUCT RANGE

Semi-Fluid & Centralised Greases

APPLICATION

- Centralised and progressive auto-lube systems
- Gearboxes designed for a slumping grease
- Long lubrication lines and small-bore tubing
- Cold weather auto-lube

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Smooth Semi-Fluid Grease**
Colour	ASTM D1500	**Dark Brown**
NLGI Classification		**0**
Thickener		**Lithium Soap**
Base Oil		**Solvent Refined Mineral Oil**
Base Oil Viscosity @ 40°C (IP 71), cSt		**180**
Worked Penetration (IP 50)		**355 to 385**
Copper Corrosion (IP 112)		**Pass**
Emcor (IP 220)		**0 : 0**
Four Ball Weld Load (IP 239) kgs		**315**
Timken OK Load (IP 326) lbs		**50**
Operating Temperature Range, °C		**-30°C to +110**

Typical values. They do not form a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0239

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063