GREASES

LITHIUM COMPLEX EP2 MOLY.

A lithium complex grease.

PRODUCT RANGE
Lithium Complex Greases

APPLICATION

- CV joints and driveshafts
- Machine tool chucks
- High load and shock loading with heat
- Plain bearings in wet and hot conditions

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Grey/Black Adhesive Grease**
NLGI Classification		**2**
Thickener		**Lithium Complex Soap**
Base Oil		**Solvent Refined Mineral Oil**
Dropping Point (IP132), °C		**260 min**
Oil Separation (IP121), %		**5 max.**
Copper Corrosion (IP112)		**Pass**
Solid lubricant content, %		**3**
EMCOR (IP220)		**0 : 0**
Four Ball Weld Load (IP239) kgs		**450**
Timken OK Load (IP326) kgs (lbs)		**20 (45)**
Oxidation Stability (IP142) 500 hrs @ 99°C Pressure Drop psi		**8 max.**
Operating Temperature Range, °C		**-20°C to +150°C Short periods to 180**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0923

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063