GREASES

LITHIUM COMPLEX EP2 PTFE.

A lithium complex grease.

PRODUCT RANGE
Lithium Complex Greases

APPLICATION

- Very high load applications
- Where a black moly grease is unacceptable
- Low friction requirements
- Mixed metal assemblies including aluminium

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Light Brown, Smooth**
NLGI Classification		**2**
Thickener		**Lithium Complex Soap**
Base Oil		**Solvent Refined Min. Oil**
Solid lubricant		**PTFE**
Dropping Point (IP132), °C		**230 min**
Copper Corrosion (IP112)		**Pass**
Mild Steel Corrosion (IP112)		**Pass**
Aluminium Corrosion (IP112)		**Pass**
EMCOR (IP220)		**0 : 0**
Four Ball Weld Load (IP239) kgs		**620**
Operating Temperature Range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0926

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063