GREASES

LITHIUM COMPLEX EP2.

A lithium complex grease.

PRODUCT RANGE
Lithium Complex Greases

150 min cSt	250 min °C	2
Viscosity @ 40°C	Dropping point	NLGI grade

APPLICATION

- Extended lubrication intervals under load
- Hot-running industrial and automotive bearings
- Wheel bearings and hub units
- Where a plain lithium grease is at its temperature limit

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

GREASES · CONTINUED

LITHIUM COMPLEX EP2.

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Smooth Adhesive Grease**
Colour	ASTM D1500	**Red or Blue**
NLGI Classification		**2**
Thickener		**Lithium Complex**
Base Oil		**Solvent Refined Mineral Oil**
Base Oil Viscosity @ 40°C (IP71), cSt		**150 min**
Worked Penetration (IP50)		**265 to 295**
Roll Stability (ASTM D1831) 100 hrs		**+30 Points Change In Penetration, max.**
Dropping Point (IP132), °C		**250 min**
Oil Separation (IP121), %		**5 max.**
Copper Corrosion (IP112)		**Pass**
EMCOR (IP220)		**0 : 0**
Water Washout (IP215) @ 79°C, %		**3**
Four Ball Weld Load (IP239) kgs		**450**
Wear Load Index		**62**
Timken OK Load (IP326) kgs (lbs)		**20 (45)**
Oxidation Stability (IP142) 500 hrs @ 99°C Pressure Drop psi		**8 max.**
Operating Temperature Range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0579

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063