GREASES

LONG LIFE BOOM GREASE.

A calcium sulphonate complex grease, the premium water-resistant chemistry, and one of the few greases where the thickener itself carries load.

PRODUCT RANGE

Calcium & Calcium Sulphonate Greases

250 cSt
Viscosity @ 40°C

260 min °C
Dropping point

2
NLGI grade

APPLICATION

- Telescopic crane booms and wear pads
- Telehandlers and aerial lifting equipment
- Telescopic excavator booms
- High load sliding contacts exposed to weather

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Off white, smooth grease**
NLGI Classification		**2**
Thickener		**Over-based calcium sulphonate**
Worked penetration		**265-295**
Viscosity @ 40°C, cSt		**250**
Dropping Point (ASTM D2265)		**260°C min**
4 Ball EP Load (ASTM D2596)		**620 kg**
Copper Corrosion (ASTM 4048)		**Pass**
Water washout (ASTM D1264), %		**2**
Timken OK Load (ASTM 2509)		**60 lbs**
Operating Temp. Range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0501

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063