TEXTILE LUBRICANTS

LUBREXEL 300W.

LUBREXEL 300W is an ester based carding and combing lubricant specifically designed to maximize fibre length and tear ratio.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- carding
- combing
- applied to fibre after the scoured wool dryer before carding
- spray application at wool dryer exit prior to binning
- drip application
- top making prior to oxidant/resin machine wash processes

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale yellow liquid**
SG @ 15°C		**0.95**
Viscosity @ 21°C		**150 – 250 secs.**
Ionic Character		**Non-ionic**
pH (10% aqueous solution)		**5 – 7**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS FG024

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063