COMMERCIAL VEHICLES

MARINE TWO STROKE.

A premium outboard two-stroke oil blended from highly refined mineral oils and synthetic ashless additives, exceeding the NMMA TC-W3 specification for clean-burning, low-smoke performance.

PRODUCT RANGE
Marine & Two-Stroke Oils

8.50 cSt	0.877	>115 °C	Blue
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Appearance

APPLICATION

- Water-cooled outboard two-stroke engines, high-output and small-cylinder alike
- Pre-mix and oil-injection systems (per equipment manufacturer mixing ratios)

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

NMMA	TC-W3
API	TD

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Blue**
Kinematic Viscosity @ 100°C, cSt		**8.50**
Specific Gravity @ 15.6°C		**0.877**
Flash Point, °C	ASTM D92	**>115**

Typical values. They do not form a specification.

PACK SIZES

Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0449

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063