COMMERCIAL VEHICLES

MARINER 40.

High quality marine diesel engine oil formulated primarily for high output, medium speed trunk piston diesel engines.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

APPLICATION

- Medium-speed trunk piston marine diesels
- Marine auxiliary engines
- Stationary high-output diesel plant

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CF-4
SAE	40 monograde

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 40**
Base Oil		**Mineral**
Density @ 15.6°C, g/cm³		**0.894**
Kinematic Viscosity @ 100°C, cSt		**12.5 – 16.3**
Flash Point, °C	ASTM D92	**> 225**
TBN, mg KOH/g	ASTM D2896	**14**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0702

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063