OFF-HIGHWAY & AGRICULTURE

MILKING MACHINE OIL.

An ISO 68 oil for the vacuum pump on a milking parlour.

PRODUCT RANGE
Agricultural Specialities

APPLICATION

- Milking parlour vacuum pumps
- Rotary and vane vacuum pumps in dairy use
- Twice-daily duty in warm, humid conditions

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity No		68
Density @ 15.6°C		0.884

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0068

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063