INDUSTRIAL OILS

MIXER MOULD OIL.

A mineral-based release oil and mixer treatment for the concrete trade.

PRODUCT RANGE
Mould Release Agents

4.8 cSt	0.8322	>62 °C
Viscosity @ 40°C	Specific gravity @15.6	Flash point

APPLICATION

- Pre-treatment of concrete and cement mixers
- Formwork release
- Plant clean-down before curing

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber fluid**
Viscosity @40°C, cSt		**4.8**
Specific gravity @15.6°C		**0.8322**
Flash Point (COC), °C		**>62**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS CM0093

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063