TEXTILE LUBRICANTS

MONOLUBE PXB.

A multi-purpose oil/synthetic textile lubricant with good wetting, anti-static and anti-mildew properties, used across fibre lubrication, conditioning and warping/beaming stages for most yarn types.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Fibre lubrication for wool and synthetic fibres at blending
- Conditioning lubricant applied during yarn winding or twisting
- Warping/beaming lubricant for weaving, as an alternative to a film-forming wax

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Yellow coloured oil**
Kinematic Viscosity @ 40°C, cSt		**21.0 - 27.0**
Active Content, %		**95-100**
Ionic Character		**Non-ionic**
Density @ 15.6°C		**0.850 - 0.870**
pH		**6.5 - 8**
Flash Point, °C	ASTM D92	**>180**
Viscosity (Redwood, emulsion 3, °C		**1): 28 - 35 secs @ 20**
Anti-static Properties		**Excellent**
Solubility		**Readily emulsifiable**

Typical values. They do not form a specification.

PACK SIZES

Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS FG050

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063