METALWORKING FLUIDS

MULTIGRIND SX FF.

A fully synthetic, formaldehyde release biocide free, watermix grinding fluid suitable for surface and cylindrical grinding on ferrous and non-ferrous materials including yellow metals, offering low foam performance and

PRODUCT RANGE
Soluble Grinding Fluids

APPLICATION

- Surface and cylindrical grinding on ferrous alloys
- Aluminium alloys
- Yellow metals
- Nickel alloys
- Aerospace alloys

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance (Concentrate)		**Green liquid**
Appearance (Emulsion)		**Green clear solution**
pH (3% emulsion)		**8.7**
IP 287 Breakpoint, %		**2.5**
Mineral Oil Content		**Nil**
Refractometer Conversion Factor		**3.2**
Make Up Water Hardness, ppm		**30 – 450**
Grinding Concentration, %		**3% – 5**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IF0411

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063