INDUSTRIAL OILS

MULTILUBE OIL 46.

An ashless multifunctional oil designed to do the job of three products at once, slideway, hydraulic and gearbox, in machines where separating them is impractical.

PRODUCT RANGE
Multi-Purpose Oils

APPLICATION

- Machines sharing one oil across slideway, hydraulic and gearbox
- Small and older machine tools
- Stock rationalisation across a workshop
- General industrial lubrication where an ashless oil is preferred

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity @ 40°C		**41 – 51**
Specific Gravity @ 15.6°C		**0.865**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS ML0046

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063