INDUSTRIAL OILS

# MULTILUBE OIL 680.

An ashless multifunctional oil designed to do the job of three products at once, slideway, hydraulic and gearbox, in machines where separating them is impractical.

PRODUCT RANGE
**Multi-Purpose Oils**

## APPLICATION

- Machines sharing one oil across slideway, hydraulic and gearbox
- Small and older machine tools
- Stock rationalisation across a workshop
- General industrial lubrication where an ashless oil is preferred

### NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Viscosity @ 40°C | | **612 – 748** |
| Specific Gravity @ 15.6°C | | **0.910** |

Typical values. They do not form a specification.

## PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

### HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS ML0680

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063