AUTOMOTIVE

MULTIVEHICLE MTF 75W80 GL-4+.

A fuel-efficient, manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and synchronizer compatibility.

PRODUCT RANGE

Manual Transmission Fluids

50.9 cSt	8.9 cSt	0.855
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6

APPLICATION

- Modern passenger car manual transmissions where gearbox and differential share the same unit

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 35 industry and OEM approvals, simplifying product consolidation

AUTOMOTIVE · CONTINUED

MULTIVEHICLE MTF 75W80 GL-4+.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4
GL-4+	
BMW	MTF LT-2
GM	1940004, 1959104, 1940764, 1940768, 1940182, W16612 (dry DCT)
FIAT	MZ1, MZ6
FORD	M2C 186-A, M2C 200-C, M2C 200-D2 (dry DCT)
Honda	Special MTF, MTF-II, MTF-III
Nissan	MT-X, MT-XZ TL (JR Type)
PSA	B71 2330 (EZL 848), B71 2315, B71 2316 (HBVFE)
Renault	DC4 DWS (dry DCT)
Volvo	97308, 97309
VW	G 052 512 (dry DCT), G 055 512 (dry DCT), G 052 171, G 052 178, G 052 726, G 060 726, G 50, G 009 317, G 052 527 A2, G 070 726 A2

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.855**
Viscosity @ 100°C, cSt	ASTM D445	**8.9**
Viscosity @ 40°C, cSt		**50.9**
Viscosity Index	ASTM D2270	**156**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0640

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063