SPECIALITIES

OAT LONG LIFE YELLOW ANTIFREEZE.

A yellow OAT long-life concentrate weighted towards the heavy-duty side of the market, carrying ASTM D6210, the heavy duty diesel coolant standard, alongside D3306, plus DAF 74002, Cummins CES 14603, MAN 324 SNF, MTU M

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Heavy duty diesel engines with wet liners
- HGV and bus fleets on long-life coolant
- Agricultural and construction plant
- Systems requiring ASTM D6210

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
DAF	74002
Cummins	CES 14603
MAN	324 Type SNF
Mercedes-Benz	325.3
MTU	MTL 5048
RENAULT	41-01-001-D
VAG	G12/G12+, TL 774-D/F
VOLVO	VCS 418-001
Suitable	for use where G30, G33 and G34 specification fluids are required

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Yellow Colour**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0562

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063