GREASES

OPEN GEAR GREASE.

A bitumen-free aluminium complex compound with solid lubricants and polymers for open gearing.

PRODUCT RANGE
Open Gear & Wire Rope

APPLICATION

- Kiln and mill girth gears
- Open gearing on cranes and draglines
- Exposed racks and pinions
- Where a bitumen compound is unwanted

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Adhesive grease**
NLGI classification		**2.5**
Base Oil		**Solvent-refined mineral oil**
Thickener		**Aluminium complex**
Copper corrosion (IP112)		**Pass**
Resistance to corrosion EMCOR (IP220)		**0 : 0**
Water washout (IP215) @39°C, %		**0**
Dropping point (IP132), °C		**>240**
Operating temp. range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0250

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063