SAR Lubricants

SPECIALITIES

PENETRATING RELEASE SPRAY.

Low-viscosity penetrant that creeps into rusted and corroded threads to break the bond, with a corrosion inhibitor left behind after release.

PRODUCT RANGE
Aerosols & Sprays

APPLICATION

- Seized and corroded fasteners
- Exhaust and chassis bolts
- Plant maintenance and shutdowns

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Workshop	grade

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Type		**Penetrating oil**
Capillary Action		**High**
Flash Point, °C	ASTM D92	**> 60**
Corrosion Protection		**Yes**
Temperature Range, °C		**-20 to +120**

Typical values. They do not form a specification.

PACK SIZES

400 ml aerosol; 500 ml aerosol; 12 x 500 ml case

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS on request

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063