TEXTILE LUBRICANTS

PERFACOLOR PM.

PERFACOLOR PM is a strongly cationic migrating and levelling agent for wool and polyamide particularly on pre-metallised dyestuffs.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- levelling and migration on wool and polyamide
- pre-metallised dyestuffs
- correction/stripping of faulty dyeings
- wash-off of acid-printed polyamide fabrics
- dyeing (light shades 1.5% O.W.F.; medium shades 1.0%; dark shades 0.5%)

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Does	not contain banned substances listed by GOTS/ZDHC
Oeko-Tex	Standard 100 and Bluesign

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear, pale straw coloured liquid**
pH (5% aqueous solution)		**8.5**
Ionic Activity		**Cationic**
Solubility		**Easily soluble in cold water**

Typical values. They do not form a specification.

PACK SIZES

25kg drums, 200kg drums, 1000kg IBC's. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0029

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063