TEXTILE LUBRICANTS

PERFACOLOR WPA.

PERFACOLOR WPA is a protein-based dyeing auxiliary designed to maintain the quality of wool textiles during aqueous processing.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- dyeing
- chroming
- acid stripping (normal treatment rate 1.0-2.0% O.W.F.; up to 4% O.W.F. under more severe conditions)

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear pale amber liquid**
pH (1% aqueous solution)		**5-7**
Ionic Activity		**Amphoteric**

Typical values. They do not form a specification.

PACK SIZES

25kg, 120kg, 200kg plastic drums, 1000kg IBC's

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0025

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063