TEXTILE LUBRICANTS

PERFAKNIT 22.

PERFAKNIT 22 is a highly efficient needle lubricant possessing good emulsion-forming properties with excellent antiwear performance, blended with hydroprocessed base oils.

PRODUCT RANGE
Knitting Oils

APPLICATION

- Lubrication of needles
- Sinkers and cams of all types of knitting machines including electronic machines
- Flat-bed machines
- Compatible with automatic oilers

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

GOTS, ZDHC, Bluesign

Oeko-Tex	Standard 100

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Bright and clear**
Colour	ASTM D1500	**Colourless to pale yellow**
Kinematic Viscosity @ 40°C, cSt		**22.8**
Density @ 15°C	ASTM D4052	**0.856**

Typical values. They do not form a specification.

PACK SIZES

25 L | 205 L | 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX004922

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063