TEXTILE LUBRICANTS

PERFALUBE SPL.

PERFALUBE SPL is a highly anti-static, water soluble lubricant for the processing of wool on the worsted system, formulated specifically to give trouble-free processing of chlorine shrink resist treated wool.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- worsted wool processing
- chlorine shrink resist treated wool processing
- carding and combing (0.2-0.4% total extractable)
- spinning (1.0-1.1% total extractable)

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Golden Liquid**
pH (1% aqueous solution)		**7 – 8**
Ionic Activity		**Non-ionic / weakly anionic**
Activity, %		**75 – 80**

Typical values. They do not form a specification.

PACK SIZES

200 kg drums, 1000 kg IBC's. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0027

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063