TEXTILE LUBRICANTS

PERFASCOUR LAN200.

PERFASCOUR LAN200 is a concentrated version of Perfascour LAN, developed for processing knitted garments manufactured in natural fibres, containing non-ionic and anionic detergents and blended buffers, designed so only o

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- scouring of knitted garments in natural fibres
- optimum scouring temperature 40-45°C
- normal application levels 3-5% owf

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear colourless liquid**
Ionic Activity		**Non-ionic/Anionic**
Specific Gravity @ 15°C		**1.030-1.080**
pH (1% aqueous solution)		**9.0-10.0**

Typical values. They do not form a specification.

PACK SIZES

120 & 200 kg drums, 1000 kg IBCs, bulk deliveries. Other pack sizes and bulk deliveries up to 25,000 litres available on request

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0020

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063