TEXTILE LUBRICANTS

PERFASOFT PJ.

PERFASOFT PJ is an aqueous micro-emulsion of amino silicone polymer developed as a single addition, resin-stable softening agent.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Padding (5-10g/ltr dilution)
- Exhaustion (0.5-1.0% at 40°C, 15-20 minutes, pH 6-6.5)
- Wool and cashmere knitwear
- Cotton
- Polyester/cotton blends
- Synthetics

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear, water-white liquid**
Solubility		**Totally water soluble**
pH (1% aqueous solution)		**4-6**
Ionic activity		**Non-ionic/cationic**

Typical values. They do not form a specification.

PACK SIZES

25kg drums, 200kg drums, 1000kg IBC's

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0012

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063