TEXTILE LUBRICANTS

PERFASOFT SS.

PERFASOFT SS is a versatile non-ionic/cationic softening and anti-static agent which gives an effective anti-static effect to most fabric types.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Last-bath softening/anti-static treatment (1-3% pH 5-6 35°C 10-20 minutes)

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White, stable emulsion**
Solubility		**Disperses readily in water**
pH (10% aqueous solution)		**4–6**
Ionic activity		**Non-ionic/cationic**

Typical values. They do not form a specification.

PACK SIZES

20 kg drums, 120 kg drums, 200 kg drums, 1000 kg IBC's

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS PX0014

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063