GREASES

# PIN & BUSH GREASE.

A tenacious, moly and graphite loaded lithium grease built for heavy plant.

PRODUCT RANGE
**Heavy Plant Greases**

## APPLICATION

- Bucket pins on excavators and loaders
- Crane slews and heavy pivots
- Assembly and running-in compound
- Fifth wheels and heavy oscillating joints

### NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

## BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Colour & Appearance | | **Grey/black, smooth, stringy grease** |
| NLGI Classification | | **2 to 3** |
| Thickener | | **Lithium soap** |
| Base Oil | | **Mineral oil** |
| Solid Lubricants | | **Molybdenum disulphide and graphite** |
| Solid Lubricants Content, % | | **16** |
| Dropping Point (ASTM D2265) | | **180°C min** |
| Dynamic Corrosion Resistance (EMCOR) (IP 220) | | **0:0** |
| Salt Water (DIN 51802) | | **0:0** |
| Copper Corrosion (IP 112) | | **Negative** |
| Oil Separation (IP 121), % | | **1** |
| Timken OK Load (IP 326) | | **22 kgs** |
| Operating Temperature Range, °C | | **-20°C to +140** |

Typical values. They do not form a specification.

## PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

### HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0903

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063