SPECIALITIES

POLAR FREEZE 1 MEG 50/50 ANTIFREEZE.

The conventional MEG coolant in ready-to-use 50:50 form.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Fleet and workshop top-ups
- Sites without reliable deionised water
- Service vans carrying ready-to-use fluid

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D3306
SAE	J1034
AFNOR	NF R15-601
BTC	Type 2
ECUNA	NC 956-16

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Blue liquid**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0962

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063