SPECIALITIES

POLAR FREEZE 3 VCS 5050.

Polar Freeze 3 VCS supplied ready mixed, protecting to -37 °C as received.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- HGV fleet servicing and roadside top-up
- Depots eliminating dilution error
- Heavy duty diesel systems on ASTM D6210

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 13 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
DAF	74002
Cummins	CES 14603
MAN	324 Type SNF
Mercedes-Benz	325.3
MTU	MTL 5048
RENAULT	41-01-001-D
VAG	G12/G12+, TL 774-D/F
VOLVO	VCS 418-001
Suitable	for use where G30, G33 and G34 specification fluids are required

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Yellow Colour**
Frost protection, °C		**Use as received, protects to -37**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0970

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063