SPECIALITIES

POLAR FREEZE 3 VCS.

The yellow heavy-duty OAT concentrate, and the grade with published frost protection figures across the dilution range: 25% gives -12 °C, 33% gives -22 °C and 50% gives -37 °C.

PRODUCT RANGE

Antifreeze & Coolants

APPLICATION

- HGV and bus fleets
- Heavy duty diesel engines requiring ASTM D6210
- Volvo VCS 418-001 systems
- Operations that dilute to their own specification

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 13 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
DAF	74002
Cummins	CES 14603
MAN	324 Type SNF
Mercedes-Benz	325.3
MTU	MTL 5048
RENAULT	41-01-001-D
VAG	G12/G12+, TL 774-D/F
VOLVO	VCS 418-001
Suitable	for use where G30, G33 and G34 specification fluids are required

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Yellow Colour**
Frost protection @ 25%, °C	SG 1.030	**-12**
Frost protection @ 33%, °C	SG 1.040	**-22**
Frost protection @ 50%, °C	SG 1.060	**-37**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0969

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063