SPECIALITIES

POLAR FREEZE 5 SI-OAT (PURPLE) 50:50 ANTIFREEZE.

The pre-mixed, ready-to-use form of the Polar Freeze Si-OAT coolant, using Organic Acid Inhibitor/Low Silicate Technology to protect from frost damage down to -38°C, free of nitrites, amines, phosphates and borates.

PRODUCT RANGE

Antifreeze & Coolants

APPLICATION

- Aluminium alloy coolant systems, ready-to-use 50:50 dilution
- Passenger cars, light and heavy commercial vehicles, off-highway plant

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 11 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
Cummins	CES 14603
MAN	324 Type Si-OAT
Mercedes-Benz	325.6
MTU	MTL 5048
SCANIA	TB 1451
VAG	G12++, TL 774-GG

40 specification fluid

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pink/Red colour**
Freeze protection @ 25% dilution, °C	S.G. 1.032	**-12**
Freeze protection @ 33% dilution, °C	S.G. 1.040	**-22**
Freeze protection @ 50% dilution, °C	S.G. 1.065	**-38**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0973

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063