SPECIALITIES

POLAR FREEZE 7 HYBRID-NF 50/50 ANTIFREEZE.

Polar Freeze 7 Hybrid-NF supplied ready to use at 50:50, protecting to -40 °C from the drum.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Depot servicing of European commercial vehicles
- Roadside top-up on nitrite-free systems
- Fleets standardising on ready-mixed coolant

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 14 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Green Colour**
Frost protection		**-40 °C as received**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306, D6210
AFNOR	NF R15-601
SAE	J 1034
Chrysler	MS-7170
Cummins	85T8-2
Deutz	DQC CA-14
FORD	ESD-M97B49-A
Iveco	Standard 18-1830
MB	325.00
MAN	324 Typ NF
SCANIA	LLC TB1451
VAG	G11, TL 774-C
Suitable	for use where G48 specification fluid is required

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0964

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063