SPECIALITIES

POLAR FREEZE 7 HYBRID-NF ANTIFREEZE.

The green hybrid-OAT concentrate in the Polar Freeze range, giving frost protection to -40 °C and formulated for heavy duty diesel work.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- European commercial vehicle fleets
- Wet liner diesels without nitrite SCAs
- MAN 324 Typ NF and MB 325.00 systems
- Deutz, Iveco and Scania plant

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306, D6210
AFNOR	NF R15-601
SAE	J 1034
Chrysler	MS-7170
Cummins	85T8-2
Deutz	DQC CA-14
FORD	ESD-M97B49-A
Iveco	Standard 18-1830
MB	325.00
MAN	324 Typ NF
SCANIA	LLC TB1451
VAG	G11, TL 774-C

G48 specification fluid

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Green Colour**
Frost protection, °C		**Protects to -40**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF00400

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063