AUTOMOTIVE

PRO-BIKE 4T 10W-40 MOTORCYCLE ENGINE OIL.

High-performance, semi-synthetic motorcycle engine oil compatible with applications incorporating wet clutch configurations.

PRODUCT RANGE
Motorcycle Oils

94.2 cSt	14.1 cSt	0.868	> 200 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Four-stroke motorcycles with wet clutches
- Shared engine, clutch and gearbox sumps
- Scooters and ATVs

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Semi-synthetic**
Kinematic Viscosity @ 40°C, cSt		**94.2**
Kinematic Viscosity @ 100°C, cSt		**14.1**
Viscosity Index	ASTM D2270	**154**
Flash Point (COC), °C		**> 200**
Pour Point, °C	ASTM D97	**-40**
Specific Gravity @ 15.6°C		**0.868**

Typical values. They do not form a specification.

PACK SIZES

1 L, 4 L, 20 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	SN, SM, SJ
JASO	MA-2

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0740

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063