METALWORKING FLUIDS

QUENCHING OIL Q22-A.

Fully accelerated cold quenching oil of low viscosity suitable for use at temperatures up to 100°C, based on solvent refined mineral oils, formulated for exceptional thermal stability with maximum resistance to oxidation

PRODUCT RANGE
Quenching Oils

23.5 cSt	0.85	200 °C
Viscosity @ 40°C	Specific Gravity	Flash point

APPLICATION

- General purpose quenching in open tanks
- Sealed furnaces
- Continuous furnaces
- Accelerated hardening of lean alloy steels

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear Pale Amber**
Viscosity @ 40°C (centistokes)		**23.5**
Specific Gravity	ASTM D1298	**0.85**
Flash Point °C (PMCC)		**200**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IQ0022A

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063