METALWORKING FLUIDS

QUENCHING OIL Q32.

Highly refined, low viscosity, low sulphur content general purpose quenching oil ensuring excellent quenching characteristics with good oxidation stability, low volatility and low drag-out losses.

PRODUCT RANGE
Quenching Oils

28.8-35.2 cSt	5.3 cSt	0.875	178 min °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @15.6	Flash point

APPLICATION

- General purpose quenching
- Optimum operating bath temperatures 25–80°C

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40°C, mm^2/s		**28.8-35.2**
Kinematic Viscosity @ 100°C, mm^2/s		**5.3**
Specific Gravity @15.6°C		**0.875**
Flash Point (PMCC), °C		**178 min**
Pour Point, °C		**-12**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IQ0032

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063